

**STANLEY® FatMax® TruLaser™ Comparison Chart --- LaserStreet.com**

<b>Technical Data</b>	<b>TLM 100</b>	<b>TLM 200</b>	<b>TLM 300</b>
Measuring Accuracy	± 1/4 in (± 6mm)	± 1/8 <sup>th</sup> in (± 3mm)	± 1/16 <sup>th</sup> in (± 1.5mm)
Range	<b>2ft - 100ft</b> (0.6 - 30m)	<b>1ft - 100ft</b> (0.3 - 30m)	<b>2in - 650ft</b> (0.05 - 200m)
Units of Measure	ft 1/8 <sup>th</sup> in, ft/100ths, in/10ths, metric	ft 1/16 <sup>th</sup> in, ft/100ths, in/10ths, metric	ft 1/32 <sup>nd</sup> in, ft/100ths, in/10ths, metric
Laser Class	Class IIIA	Class 2M	Class 2M
Distance, Area, Volume Calculations	•	•	•
Addition & Subtraction	•	•	•
Continuous Measuring (tracking)		•	•
Min/Max Distance Tracking		•	•
Pythagoras Function (indirect height/width)		2-Point	2-Point, 3-Point
Trapezoid Measuring			•
Time Delay Release			•
Built-in Telescopic Viewer			•
Built-in Bubble Level			•
Universal Tripod Mount			•
Splash proof/ Dust proof	Low	•	•
Multifunction End Piece			•
Backlit Display		•	•
Memory Storage			20 Values
Keyboard	Rubber	Foil Keypad	Soft-Touch
Wrist Strap			•
Holster	•	•	•
Batteries Life (no. of measurements)	up to <b>2,000</b>	up to <b>5,000</b>	up to <b>10,000</b>
Battery Type (Qty)	9V (1)	AAA (2)	AA (2)
Manufacture's Warranty	1 Year	1 Year	2 Years
<b>List Price</b>	<b>\$99.00</b>	<b>\$249.00</b>	<b>\$449.00</b>